


8G30H-DEKA

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	108Ah
Capacity at C/20	97.6Ah
Weight	70 lbs. (31.8 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) - 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.30 - 2.35VPC
Float	2.25 - 2.30VPC
Vent	Self-sealing
Electrolyte	Sulfuric acid thixotropic gel
Terminal	B (T876)




Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co, Inc.

Distributed by:


Valve-Regulated, Gelled-Electrolyte Battery



DIMENSIONS

Length (mm)	12.93 (329 mm)
Width (mm)	6.75 (171 mm)
Height (mm)	9.76 (248 mm)

Gel Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



WholeSolar

P.O. Box 178799
San Diego CA 92177

(760) 505-0054
(858) 581-2126 Fax
<http://www.whole-solar.com>